

Superiorseal Primer

Description

Superiorseal Primer can be applied to eliminate darkening of the surfaces prior to applying Superiorseal 2 K Systems.

If a paint or coating has been applied to the surface, Superiorseal Primer is not required.

Properties

Product Number	M570 & M571
Appearance	Milky white liquid
System	Single Pack
Odour	Mild
Solids Volume	24-28%
Dry Film Clarity	Excellent – Not tinted
Specific Gravity	1.0
Viscosity	~80 cp
Flammability	Non-Flammable
pH	8-10
Pot Life	3-4 Hours
Dry Time	10-30 Minutes
Curing Time	24 Hours
VOC Content	65 g/L
UV Resistance	Excellent
Resistances	Alkaline Grease Oil



Superiorseal Primer

Application

Preparation

- If coating externally ensure weather conditions are suitable for application
- Surface to be coated must be free from dust, oil, grease
- Do not apply if temperatures are less than 10 °C or greater than 30 °C
- Surface can be damp but not wet

Coating

- Mix well before use
- Surface can be damp but not wet
- Apply with a good quality roller or low-pressure spray
- We recommend applying 1 coat of Superiorseal Primer.
- It is important to ensure the whole surface is evenly coated as missed parts will darken when Superiorseal 2 K systems are applied.

Clean Up

Clean any tools used in the application process with water immediately after use.

Storage

Store in a well-ventilated cool location between 10 °C and 30 °C.

Keep sealed when not in use.

Packaging

Volume (L)	Container
5	Jerry
20	Cube

Coverage

	Uncoated Surfaces (m ² /L)
First Coat	8-10
Second Coat	10-12

Safety

Always wear appropriate PPE while handling the product.

Please Note: This information is based on current knowledge. It does not constitute a guarantee and we recommend that testing should be undertaken to ensure that the final result is satisfactory for the intended application. The quality of the product is guaranteed under our General Conditions of Sale.

